This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

(30) Priority data:

1990/15860 U

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:		(11) International Publication Number:	WO 92/06734
A61M 29/00	A1	(43) International Publication Date:	30 April 1992 (30.04.92)

KR

(21) International Application Number: PCT/KR91/00023

17 October 1991 (17.10.91) (22) International Filing Date:

18 October 1990 (18.10.90)


1991/5271 U 17 April 1991 (17.04.91) (71)(72) Applicant and Inventor: SONG, Ho, Young [KR/KR]; 803, Keosung Kosok-mansion, 1168-2, Jinbuk-dong, Cheonju-si, Cheonrabuk-do 560-160 (KR).


(74) Agents: JUN, Chai, Hoon et al.; 702, Teheran Bd., 825-33, Yoksam-dong, Kangnam-ku, Seoul 135-080 (KR).

(81) Designated States: AT (European patent), AU, BE (European patent), CA, CH (European patent), DE (European pean patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP (Utility model), LU (European patent), NL (European patent), NO, SE (European patent), US.

Published With international search report.

(54) Title: SELF-EXPANDING ENDOVASCULAR STENT





(57) Abstract

An object f this invention is to provide a radially expandable stent (1) that holds a passageway enlarged by placing the stent (1) into a lumen. The stent (1) comprises a cylindrical frame formed by a plurality of unit structures (11, 12,... 16,...); said unit structures (11, 12,... 16,...) formed into a closed zig-zag configuration including an endless series of straight sections (111) and joined by bends (112), and arranged face to face into a shape of multistage; connecting members (31, 33, 35, 37...), which connect said unit structures (11, 12,... 16,...); and a mesh (91), which is wrapped around an outside of said frame.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madapatear
AU	Australia ·	FI	Finland	ML	Mali
22	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
SF ·	· Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinga	NL.	Netherlands
BJ	Benin	GR	Groce	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland .
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CC	Congo	KP	Democratic People's Republic	SE	
CH	Switzerland		of Korea	SN.	Sweden
CI ·	Côte d'Ivoire	KR	Republic of Korea	SU+	Senegal Soviet Union
CM	Cameroon	Li	Liechtenstein	TD	
CS	Czechoslovakia	LK	Sri Lanka		Chad
DE.	Germany	ū	Luxemboure	TG	Togo
D.V	Dunmant		President E	US	United States of America

⁺ Any designation of "SU" has effect in the Russian Federation. It is not yet known whether any such designation has effect in other States of the former Soviet Union.

1

SELF-EXPANDING ENDOVASCULAR STENT

Technical Field

5 This invention relates to improvements of endovascular stent

Background Art

15

20

25

It is desirable in various situations that means be provided for expanding a constricted vessel portion or for maintaining an open passageway through a vessel portion.

For example, these situations can be those by esophageal strictures that are caused by esophageal carcinoma or esphageal metastasis, or those by strictures that resulted from the cancer of biliary system, urinary duct system and bronchial system.

The balloon expansion has been well known method of enlarging and maintaining the passageway of esophagus in these cases, but this method should be operated repeatedly for its temporary effects, and also it has no effects on the patients of serious strictures.

As alternatives, various artificial-esophagi have been used in the cases of esophageal strictures, but since they have no constriction and relaxation, the rate of esophageal rupture is high (30 - 40%) in the process of inserting them into the strictural area that has been caus d by the cancer, and the high mortality rate

2

du to mediastinitis results from rupture f sophagus. In addition, the patient has a great difficulty in swallowing due to narrow inner diameter (10 - 12 mm) of artificial esophagus, and obstruction of artificial-esophagus occurred frequently due to food intake.

As the means of overcoming the difficulty, a device to hold the passageway enlarged using a stent was presented by U.S. patent No. 4,214,587. However, th device of the invention has the temporary effect in enlarging the passageway, there is still the problem that the endovascular lumen gets narrows after a long time.

10

15

20

25

To improve this disadvantages, U.S. patent No. 4,580,568 was offered. The stent of said invention a wire formed closed into а includes configuration including an endless series of straight sections joined by bends. The stent is resiliently compressible into a smaller first shape wherein the straight sections are arranged side-by-side and closely adjacent one another for insertion into a larger second shape wherein said straight sections press against the walls of the passageway to maintain it open.

However, in a case that the stent of the 4,580,568 invention is put into use for a long time, it still has the problem that the lumen is narrowed, because the proliferated cells cover the stent thickly. There is no effect in the case of the stricture by canc r, b caus the canc r cells can pass thr ugh th straight secti ns.

المنتفأ كاحب

10

15

20

25

Discl sure of Invention

In view of the foregoing, it is the main object of this invention to provide a self-expanding endovascular stent, which expands a constricted vessel portion and maintains an open passageway through a vessel portion for a long time without moving in a lumen.

It is another object of the present invention to provide a self-expanding endovascular stent, which prevents the cancer cells to penetrate into a stent.

To accomplish said purposes, this invention provides, a stent, which comprises a cylindrical frame formed by a plurality of unit structures;

said unit structures formed into a closed zig-zag configuration including an endless series of straight sections and joined by bends, and arranged face to face into a shape of multistage; connecting members, which connects said unit structures one another and a mesh, which is wrapped around an outside of said frame.

And another stent according to the present invention comprises a cylindrical frame formed by a plurality of unit structures; said unit structures formed into a closed zig-zag configuration including an endless series of straight sections, joined by bends, and arranged face to face into a shape of multistage; connecting members, which connects said unit structures one anoth r; anti-migration members, which have the same structur with said unit structur, and placed in the ends of the upper and lower portions of said fram; and

a m sh, which is wrapped around an outsid of said fram .

Brief Description of Drawings

5

25

- Fig. 1 is a development figure that illustrates a unit structure of a frame according to the present invention.
- Fig. 2 is a perspective view of a first embodiment

 that illustrates a frame according to the present invention.
 - Fig. 3 is a development figure of said frame of the first embodiment of the invention.
- Fig. 4 is a perspective view of the first embodiment according to the invention.
 - Fig. 5 is a view of showing a state that a stent of the first embodiment according to the present invention is placed and enlarged in a lumen.
- Fig. 6 is a perspective view of a second embodiment according to the present invention that illustrates a frame.
 - Fig. 7 is a view of showing a state that a stent of the second embodiment of the present invention is placed and enlarged in a lumen.

Best Mode for Carrying out the Invention

For th purpose of promoting an understanding of

the principl s of the invention, ref rence will now be made to the embodiments illustrated in the drawings and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended, such alterations and further modifications in the illustrated device, and such applications of the principles of the invention as illustrated therein being contemplated as would normally occur of one skilled in the art to which the invention relates.

5

10

15

20

25

rig. 1 is a development figure that illustrates the unit structure of a frame according to the present invention; Fig. 2 is a perspective view of the first embodiment that illustrates a frame according to the present invention; Fig. 3 is a development figure of said frame of Fig. 2.

A frame 10 of the first embodiment comprises a reasonable number of unit structures 11 as shown in Fig. 1. The unit structure 11 is constructed of a wire, and the wire is preferably made of stainless steel. The unit structure 11 is formed into a closed zig-zag configuration, thereby forming a series of straight sections 111 and bends 112 as shown in Fig. 1. Both ends of the wire are joined to each other by welding, thereby forming an endless series of straight sections joined by bends.

frame 10 is constructed in a way that a plurality of said unit structures 11 cl sely similar to ach other and bends corresponding t ach of the unit

5

10

15

20

25

structur s are arranged face to face into a shape of a multistage. At this tim , every unit structure is connected in tandem by a reasonable number of connecting members 31, 33, 35, 37, ---. These connecting members are joined appropriately between the bends of appointed unit structure such that they prevent each unit structure from being separated. The most preferable joint position of the connecting members is to be placed diagonally, regarding the connecting member 31 as a fiducial point as shown in Fig. 3. Namely, it is preferable to have a construction 31, 33, 35, and 37 as can be seen in Fig. 3. Also, the connecting members are not connected with every other bend and the frame 10 wherein an appropriate number of connecting members in one unit structure 11 i. e. ten connecting members in the first embodiment of Fig. 3 are connected to each other, has a plurality of diamond-like spaces 100. number of the unit structure or the connecting members do not have a special meaning, and may be varied according to a state of a patient and/or convenience of production.

The space areas receive the straight section 111 when the straight section 111 is shrinked, making an elasticity variation with the bend 112.

A completed frame 10 has anti-migration members 41, 43 for preventing migration of a stent in a lumen that are equipped with barbs that jut outsid. The anti-migration members 41, 43 are properly arrang d and connect d with the bends which the connecting members

10

15

20

25

31, 33, 35, 37 are not connected. Th refor , th stent 1 of th pr s nt invention do s not move in a lumen.

All the unit structures, the connecting members, and the anti-migration members are made of the same material like stainless steel, preferably are gilt.

The frame 10 is wrapped in a mesh 91, and upper and lower hem of the mesh 91 are folded towards inside, and both hems become respectively adhesive whereby a wire of the unit structure 11 is not exposed. It is preferable that the mesh is made of nylon and the nylon mesh is coated with silicon rubber.

The method of 587 U.S. patent or a method using a catheter in which the stent of the invention being compressed may be used in order to place the stent of the present invention at a position, namely a diseased part in a lumen.

The stent is fixed on inner walls of the lumen with the barb 411 of the anti-migration member, and though the stent is used for a long time, it does not migrate, and in addition thereto, pain that a patient may feel can be relieved, compared with conventional stent, because an outer wall of the stent 1 is wrapped with mesh 91. Furthermore, the silicon rubber coating on the mesh 91 can prevent that cancer cell and the like penetrate into the inside of the stent.

As a result of experimenting the first embodiment f this invention on patients with gastric cancer or sophageal cancer, following ffects are brained.

A. A patient with gastric cancer and sophag al

10

15

20

25

نغندنا أوران

spr ading of gastric canc r came to Hospital of Cheon Buk Medical Colleg on July, 1989. The symptoms of the patient were improved after six times medicine of anti-cancer. But the patent revisited to the medical college for an appearance of a dysphagia.

On January 8, 1990, an obstructed area of distal portion of esophagus due to spreading of gastric cancer, was enlarged with an esophageal balloon of 20 mm in diameter and 8 cm in length, and then a stent of 20 mm in external diameter and 8 cm in length was intubated into a strictural area of esophagus through a sheath of 10 mm.

After operation, the patient was able to eat liquid food and solid food, and in esophagogram performed in seven days after operation, a balium passed well through esophagus without any undercurrent or obstruction, and specific complications such as the migration of the stent or the rupture of the esophagus, did not occur.

After that, the patient left the hospital, and died of a generalized metastasis of gastric cancer on April, 1990. However, there was no problem with the function of the stent until just before the patient's death.

B. A patient with gastric cancer and esophageal metastasis came to Hospital of Cheon Buk Medical College owing to dysphagia on March 13, 1990.

After an obstructed portion of esophagus was enlarged with an esphageal ball on of 20 mm in diamet r and 8 cm in length, a stent of 20 mm in external

diam t r and 10 cm in length was intubat d into th distal portion of esophagus through th sheath of 10 mm in external diameter.

As a result of the operation, the patient was not able to eat even water, but after the stent was intubated into his lumen, the patient was able to taking the liquid food and solid food, and a balium passed well through without any undercurrent or obstruction in esophagogram performed in seven days after the operation. When endoscope is performed on March 27, 1990, the endoscope of 10 mm in external diameter was passed through without any difficulty.

5

10

15

20

25

And in following up examination of esophagogram performed on August 10, 1990, any specific complications like the moving or the obstruction of the stent did not occur, and in addition, the patient was able to eat the liquid food and solid food.

C. A patient with the esophageal carcinoma was hospitalized in the Hospital of Cheon Buk Medical College, and took radiotherapy and medicated anti-cancer medicine five times, and then symptoms were improved, but the patient revisited to the hospital due to the dysphagia.

After the obstructed area of the esophagus was dilated with the esophageal balloon of 20 mm in diameter and 8 cm in length, the stent of 20 mm in external diamet r and 12 cm in 1 ngth was intubated into the obstruct d ar a of the esophagus through th 10 mm sheath.

10

15

20

25

As a result of the tratment, the patient was able to eat liquid f d and solid food, balium pass d well through without any undercurrent or obstruction in esophagogram, and any complication like the migration of the stent or the rupture of the esophagus did not occur.

As medical appliance of the present invention is proved by the experiment on the above, since the expansile force of the stent that is intubated into an appointed area and is kept, is excellent, the outstanding effects that keep the stricture of passageway enlarged can be obtained.

The construction of the first embodiment as mentioned above is expected of preventing the migration of the stent, but since the distal ends of the anti-migration members 41, 43 have barbs that jut out externally, the possibility cannot be excluded that the barbs cause a patient to feel pain and lumen perforation, and when the stent is artificially transferred to set the position of the stent to rights, the lumen wall can be hurt.

Fig. 6 is a perspective view of a second embodiment of the present invention, and shows that a plurality of unit structures 21, 22, 23, 24 are linker, being expanding. The unit structures 21, 22, 23, 24 are identical with the unit structures of the first embodiment.

According to the second embodiment of this invention, the stent comprises the frame 20 formed by a plurality of connected unit structur s 21, 22, 23, 24,

10

15

20

25

and anti-migr tion members 42 and 44 plac d in lower and upper portions of the frame 20. The frame 20 without anti-migration members 42 and 44 is almost same with the frame of the first embodiment of this invention except for the numbers of the unit structures and the length of connecting members 36, 38. The numbers of unit structures have no meaning in this invention. And the length of connecting members 36, 38 in the ends of the upper and lower portions of the frame 20 is a half of the length of the connecting members 31, 39 of the first embodiment of this invention.

The both side sections of the unit structures 21, 24 are connected with the anti-migration members 42 and 44 through the second connecting members 32, 34.

Anti-migration members 42 and 44 placed in the ends of the upper and lower portions of the frame 20 have the same structures with the unit structures 21, 22, 23, 24. But the anti-migration members 42 and 44 are formed to be larger than the frame 20 in diameter. To connect the frame 20, and the anti-migration members 42 and 44, that are different from each other in diameter, is available through the second connecting members 32, 34. The second connecting member 34 connects a bend 381 or the end 381 of the connecting member 38 with a bend 442 of the anti-migration member 44. This connection is performed by welding.

Since the diameter of the anti-migration members 42 and 44 d pends on the length of horizontal parts 321, 341 of the s cond connecting m mbers 32, 34, it is

10

important to d termine th length thereof. Expansile parts 322, 342, expand d from th horizontal parts 321, 341 and bended vertically.

It is omitted in Fig. 6 that a mesh is wrapped around the outside of the frame 20.

The stent 2 formed as mentioned above keeps expanded unless force is given thereto. In order to place the stent within an esophagus, a given introducing assembly such as an introducing tube, an esophageal balloon and a pusher catheter are pushed into a stricture in a compressed state.

As the introducing tube is removed over the pusher catheter, the compressed stent is automatically passed through and expanded.

15 Fig. 7 is an explanatory view of the state that the stent 2 placed within a lumen is radially expanded to stick to the lumen.

A stent that can be used for patients with esophageal carcinoma is described above, and if a stent was formed to be cylindrical between 8 mm to 10 mm in diameter, other applications of the stent are in the biliary, bronchial and urinary systems.

20

20

25

CLAIMS.

1. A stent comprising:

a cylindrical frame 10 formed by a plurality of unit structures 11, 12, 13, 14, 15, 16;

said unit structures 11, 12, 13, 14, 15, 16 formed into a closed zig-zag configuration including an endless series of straight sections 111 and joined by bends 112, and arranged face to face into a shape of multistage;

connecting members 31, 33, 35, 37, which connects said unit structures 11, 12, 13, 14, 15, 16;

and a mesh 91, which is wrapped around an outside of said frame 10.

- 2. A stent as claimed in claim in 1 wherein anti-migration members 41, 43 with barbs are installed in a central area 100 of said frame 10.
 - 3. A stent as claimed in claims 1 and 2 wherein said frame 10, connecting members 31, 33, 35, 37, and anti-migration members 41, 43 are gilt.
 - 4. A stent as claimed in claims 1 and 2, wherein said mesh 91 coated with silicon rubber.
 - 5. A stent comprising:
 - a cylindrical frame 20 formed by a plurality of unit structures 21, 22, 23, 24;

said unit structures 21, 22, 23, 24 formed into a closed zig-zag configuration including an endless series f straight sections 211, joined by bends 212, and arranged face to face into a shape of multistage;

connecting memb rs, which connects said unit structures 21,22, 23, 24;

anti-migration members 42 and 44, which have same structures with said unit structure, and placed in the ends of the upper and lower portions of said frame;

and a mesh, which wrapped around an outside of said frame 20.

- 6. A stent as claimed in claim in 5, wherein said anti-migration members 42 and 44 have larger diameters than the diameter of said frame 20, and connected to said frame 20 by the second connecting members 32, 34.
- 7. A stent as claimed in claim 6, wherein the second connecting members 32, 34 consisting of vertical parts 321, 341 and expansile parts 322, 342.
- 8. A stent as claimed in claims 5, 6 and 7, wherein a mesh wrapped whole around an outside of said frame 20 and anti-migration members 42 and 44.
 - 9. A stent as claimed in claims 5 and 6, wherein said frame 20 and anti-migration members 42, 44 are gilt.
 - 10. A stent as claimed in claims 5 and 8, wherein said mesh coated with silicon rubber.

20

10

1/3

FIG.1





FIG.2







FIG.4



3/3

FIG.5




FIG.6





FIG.7



INTERNATIONAL SEARCH REP RT

International Application No PCT/KR 91/00023

I. CLASSIFICATION F SUBJECT MATTER (if several classification symbols apply, indicate all) *							
According to International Patent Classification (IPC) or to both National Classification and IPC							
	. Cl. ⁵ : A 61 M 29/00						
II. FIELD	S SEARCHED Minimum Docume	entation Searched 7					
Classificati	on System	Classification Symbols					
Int.	Int. Cl. ⁵ : A 61 M 29/00; A 61 F 2/04; A 61 M 25/00						
	Documentation Searched other to the Extent that such Document	than Minimum Documentation a are included in the Fields Searched ⁶					
			· .				
	IMENTS CONSIDERED TO BE RELEVANT		Relevant to Claim No. 13				
Category *	Citation of Document, ⁵¹ with Indication, where app	propriets, of the relevant passages "	Parateur in Civilli Mo. 14				
A	US, A, 4 733 665 (PALMAZ) 29 (29.03.88), see especially f 5 line 24 to column 6, line	igures 1A,1B; column	(1,5)				
A	DE, B, 1 766 921 (NAT. RES. (15.01.70), see especially f claims 1,2,9,11,13,14.	(1,5)					
A	US, A, 4 580 568 (GIANTURCO) (08.04.86), see especially f lines 37 to 68; column 3, li	(1,5)					
"T" later document published after the international filing date or priority date and not in conflict with the application but closed to be of particular relevance. "E" earlier document but published on or after the international filing date or priority date and not in conflict with the application but closed to be of particular relevance. "E" earlier document but published on or after the international filing date or priority date and not in conflict with the application but closed to understand the principle or theory underlying the connection of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive attep and the document of particular relevance; the claimed invention cannot be considered to involve an inventive attep and the document is combined with one or more other such document, such combination being obvious to a person skilled in the art. "A" W. CERTIFICATION							
Date of the	Actual Completion of the International Search	Date of Mailing of this International Ser	irch Report				
17 J	January 1992 (17.01.92)	24 January 1992 (24	.01.92)				
internation	al Searching Authority	Signature of Authorized Officer					
TRITA	TRIAN PATENT OFFFICE	Velustur Hel	العالم				

ZUM INTERNATIONALEN KECHERCHENbericht über die internationale Patentanmeldung Nr. to the International Search Report to the International Patent Application No.

au rannort de recherche inter-national relatif à la demande de brevet international n°

PCT/KR 91/00023

In diesem Anhang sind die Mitglieder der Patentfamilien der im obengeder Patentfamilien der im obengemannten internationalen Recherchenbericht cited in the above-mentioned interangeführten Patentdokumente angegeben. Diese Angaben dienen nur zur Unter-richtung und erfolgen ohne Gewähr.

This Annex lists the patent family in no way liable for these particulars which are given serely for the purpose of information.

La présente annexe indique les membres de la famille de brevets
relatifs aux documents de brevets cités
dans le ramport de recherche international visée ci-dessus. Les reseignements fournis sont donnés à titre indicatif et n'engagent pas la responsibilité de l'Office.

la Recherchenbericht angeführtes Patentdokument Patent document cited in search report Document de brevet cité dans le rapport de recherche	Datum der Veröffentlichung Publication date Date de publication	Mitglied(er) der Patentfamilie Patent family member(s) Mesbre(s) de la famille de brevets	Datum der Veröffentlichung Publication date Date de publication	
US-A - 4733665	29-03-88	AT-E - 60500 AU-A1-64882/86 AU-B2- 591942 BR-A - 8605658 DE-CO - 3677321 EP-A2- 221570 EP-TD- 221570 EP-A3- 221570 EP-B1- 221570 JP-A2-62231657 ZA-A - 8608414 US-A - 4739762 US-A - 4776337	15-02-91 14-05-87 21-12-89 15-12-87 07-03-91 13-05-87 17-12-87 23-12-87 30-01-91 12-10-87 30-04-88 11-10-88	
DE-B - 1766921		DE-A - 1766921	15-01-70	
US-A - 4580568	08-04-86	AT-E - 64538 AU-A1-48113/85 AU-B2- 581464 CA-A1- 1245527 DE-CO- 3583276 DK-AO- 4458/85 DK-A - 4458/85 EP-A2- 177330 EP-A3- 177330 EP-B1- 177330 JP-A2-61087540	15-07-91 10-04-86 23-02-89 29-11-88 25-07-91 01-10-85 02-04-86 09-04-86 24-09-86 19-06-91 02-05-86	